

**0223**

Cassaforma per calcestruzzo
Wall box for concrete

9 x 9 x H 9 cm

**0224/Q**


Piastrelle per muratura
Plaster kit

9 x 9 x H 0,7 cm


**0225**

Cassaforma per muratura
Wall box for masonry

9 x 6 x H 9 cm



Installazione senza cassaforme
Installation without wall box



Installazione senza cassaforme
Installation without wall box

I drivers 0136/15, 0125 e 0128 possono passare dal foro incasso del faretto.

Drivers 0136/15, 0125 and 0128, can pass through the recessed hole of the spotlight.



La presente scheda tecnica è di proprietà di EGOLUCE srl. Tutti i diritti sono riservati. Le fotografie, le descrizioni degli apparecchi, disegni quotati ed i valori fotometrici menzionati sono a titolo indicativo e non costituiscono alcun impegno per la nostra società che si riserva di apportare, in qualsiasi momento e senza preavviso, tutte le modifiche che riterrà opportune.

EGOLUCE s.r.l. via I.Newton 12 - 20016 Pero - Milano
telefono +39 02 339586.1 - fax. +39 02 3535112
e-mail: info@egoluce.com - http://www.egoluce.com

drivers

LED DRIVERS in corrente continua LED DRIVERS constant current

0125

LED driver
IN: 100 - 240V
OUT: 350 mA
1 COB LED




6 x 3,5 x 2 cm 4 cm

SEL

0128

LED driver
IN: 100 - 240V
OUT: 350 mA
1-2 COB LED




11,6 x 3,4 x 2 cm 4 cm

SELV CLASS 2

0136/15

LED driver
IN: 100 - 240V
OUT: 350 mA
1-2 COB LED




15,8 x 2,2 x 2 cm 3,2 cm

SELV

0169/50

Multipower LED driver

IN: 220 - 240V
OUT: 350mA
1-3 COB LED




13 x 7,5 x 3 cm 8,5 cm

SELV

DRIVERS DIMMERABILI in corrente continua DIMMABLE LED DRIVERS constant current

0129 Dimmer LED


Multipower dimmable driver
IN: 110 - 240V
OUT: 350 mA, 1-2 COB LED



10,5 x 7 x 2,2 cm 7,2 cm SELV

0129/DALI Dimmer LED

Multipower dimmable driver
IN: 110 - 240V
OUT: 350 mA 1-2 COB LED




10,5 x 7 x 2,2 cm 7,2 cm

SELV

0141/DALI


LED driver
IN: 110 - 240V
OUT: 350 mA, 1-2 COB LED



11,1 x 5,2 x 2,5 cm 5,5 cm

0141/DIM

LED driver
IN: 110 - 240V
OUT: 350 mA, 1-2 COB LED




Versione PUSH non sincronizzabile - PUSH version not synchronizable

11,1 x 5,2 x 2,5 cm 5,5 cm

0145 Dimmer LED Maxi

Multipower dimmable driver

IN: 110 - 240V
OUT: 350 mA, 1-3 COB LED




12,3 x 8 x 2,2 cm 8,4 cm SELV

0145/DALI Dimmer LED Maxi

Multipower dimmable driver

IN: 110 - 240V
OUT: 350 mA, 1-3 COB LED



12,3 x 8 x 2,2 cm

8,4 cm SELV

0133


Cavo di sincronizzazione per dimmer LED
Synchronization cable for dimmer LED
(art. 0129 - art. 0129/DALI - art. 0145 - art. 0145/DALI)
L 150 cm



0726/DIM

LED dimmer

TAGLIO DI FASE (IGBT-TRIAC, TRAILING EDGE-LEADING EDGE)
PHASE CUT-OFF (IGBT-TRIAC, TRAILING EDGE-LEADING EDGE)
IN: 220 - 240V
OUT: 24V - 20W
350 mA, 1-2 COB LED



16,5 x 4,5 x 3,5 cm 5,6 cm


IGBT-TRIAC SELV

0733/DIM

LED dimmer

Alimentatori elettronici dimmerabili (IGBT-TRIAC) in corrente continua
Direct current dimmable (TRAILING EDGE-LEADING EDGE) electronic drivers

IN: 220 - 240V
OUT: 350 mA, 1 COB LED



8,7 x 3,8 x 2,1 cm 4,2 cm


IGBT-TRIAC SELV

IP LED DRIVERS in corrente continua IP LED DRIVERS constant current

0031/IP

LED driver

IN: 220 - 240V
OUT: 350 mA
1-2 COB LED



3,9 x 8 x 2 cm 4,2 cm

IP67 SELV

