








drivers x COB LED 3x1W 350mA

Codice
Articolo**LED DRIVERS** in corrente continua
LED DRIVERS constant current**0125****LED driver**
IN: 100 - 240V
OUT: 350 mA
1 - 2 COB LED6 x 3,5 x 2 cm  4 cmSELV **0128****Multipower LED driver**
IN: 100 - 240V
OUT: 350 mA
1 - 3 COB LED11,6 x 3,4 x 2 cm  4 cm 
SELV CLASS 2**DRIVERS DIMMERABILI** in corrente continua
DIMMABLE LED DRIVERS constant current**0141/DIM**
LED driverIN: 110 - 240V
OUT: 350 mA, 1 - 4 COB LED


Versione PUSH non sincronizzabile - PUSH version not synchronizable

11,1 x 5,2 x 2,5 cm  5,5 cm    **0141/DALI****LED driver**
IN: 110 - 240V
OUT: 350 mA, 1 - 4 COB LED11,1 x 5,2 x 2,5 cm  5,5 cm   **0145 Dimmer Led Maxi**
Multipower dimmable driverIN: 110 - 240V
OUT: 350 mA, 1 - 7 COB LED12,3 x 8 x 2,2 cm  8,4 cm SELV    Codice
Articolo**0145/DALI Dimmer Led Maxi**
Multipower dimmable driverIN: 110 - 240V
OUT: 350 mA, 1 - 7 COB LED

12,3 x 8 x 2,2 cm

 8,4 cm SELV     **0133**Cavo di sincronizzazione per dimmer LED
Synchronization cable for dimmer LED
(art. 0145 - art. 0145/DALI)

L 150 cm

IP LED DRIVERS in corrente continua
IP LED DRIVERS constant current**0031/IP****LED driver**
IN: 220 - 240V
OUT: 350 mA
1 - 4 COB LED

3,9 x 8 x 2 cm

 4,2 cm IP67 SELV

La presente scheda tecnica è di proprietà di EGOLUCE srl. Tutti i diritti sono riservati. Le fotografie, le descrizioni degli apparecchi, disegni quotati ed i valori fotometrici menzionati sono a titolo indicativo e non costituiscono alcun impegno per la nostra società che si riserva di apportare, in qualsiasi momento e senza preavviso, tutte le modifiche che riterrà opportune.

EGOLUCE s.r.l, via I.Newton 12 - 20016 Pero - Milano
telefono +39 02 339586.1 - fax. +39 02 3535112
e-mail: info@egoluce.com - http://www.egoluce.com