



## drivers

**LED DRIVERS** in corrente continua  
**LED DRIVERS** constant current**0127****LED driver**  
IN: 100 - 240V  
OUT: 500mA  
1-6 Power LED

11,6 x 3,4 x 2 cm 4 cm




SELV CLASS 2


**0169/50****Multipower LED driver**IN: 220 - 240V  
OUT: 500mA  
4-15 Power LED

13 x 7,5 x 3 cm 8,5 cm


SELV

**DRIVERS DIMMERABILI** in corrente continua  
**DIMMABLE LED DRIVERS** constant current**0129 Dimmer LED****Multipower dimmable driver**IN: 110 - 240V  
OUT: 500mA,  
1-14 Power LED


10,5 x 7 x 2,2 cm 7,2 cm SELV

**0129/DALI Dimmer LED****Multipower dimmable driver**IN: 110 - 240V  
OUT: 500mA  
2-12 Power LED

10,5 x 7 x 2,2 cm 7,2 cm SELV


**0141/DALI****LED driver**IN: 110 - 240V  
OUT: 500mA,  
1-11 Power LED

11,1 x 5,2 x 2,5 cm 5,5 cm


**0141/DIM****LED driver**IN: 110 - 240V  
OUT: 500mA,  
1-11 Power LED

Versione PUSH non sincronizzabile - PUSH version not synchronizable

11,1 x 5,2 x 2,5 cm 5,5 cm

**0145 Dimmer LED Maxi****Multipower dimmable driver**IN: 110 - 240V  
OUT: 500mA,  
1- 21 Power LED

12,3 x 8 x 2,2 cm 8,4 cm SELV


**0145/DALI Dimmer LED Maxi****Multipower dimmable driver**IN: 110 - 240V  
OUT: 500mA,  
1- 21 Power LED

12,3 x 8 x 2,2 cm

8,4 cm SELV


**0133**Cavo di sincronizzazione per dimmer LED  
Synchronization cable for LED dimmers  
(art. 0129 - art. 0129/DALI - art. 0145 - art. 0145/DALI)

L 150 cm

**IP LED DRIVERS** in corrente continua  
**IP LED DRIVERS** constant current**0143/IP****LED driver**  
IN: 220 - 240V  
OUT: 500mA  
1-7 Power LED

8,2 x 3,9 x 2 cm 4,5 cm

SELV IP67

EGOLUCE s.r.l., via I.Newton 12 - 20016 Pero - Milano  
telefono +39 02 339586.1 - fax. +39 02 3535112  
e-mail: info@egoluce.com - http://www.egoluce.com