

## drivers

**LED DRIVERS** in corrente continua  
**LED DRIVERS** constant current**0125**


**LED driver**  
IN: 100 - 240V  
OUT: 350 mA  
1-6 Power LED 1W




6 x 3,5 x 2 cm  4 cm

SELV **0128**


**LED driver**  
IN: 100 - 240V  
OUT: 350 mA  
1-10 Power LED 1W




11,6 x 3,4 x 2 cm  4 cm

SELV CLASS 2  **0136/15**


**LED driver**  
IN: 100 - 240V  
OUT: 350 mA  
1-10 Power LED 1W



15,8 x 2,2 x 2 cm  3,2 cm

SELV  **0169/50****Multipower LED driver**


IN: 220 - 240V  
OUT: 350mA  
min.4-max22 Power LED 1W



13 x 7,5 x 3 cm  8,5 cm

SELV **DRIVERS DIMMERABILI** in corrente continua  
**DIMMABLE LED DRIVERS** constant current**0129 Dimmer Led**  
**Multipower dimmable driver**


IN: 110 - 240V  
OUT: 350 mA, 4-15 Power LED






10,5 x 7 x 2,2 cm  7,2 cm SELV    

**0129/DALI Dimmer Led****Multipower dimmable driver**


IN: 110 - 240V  
OUT: 350 mA, 2-12 Power LED




10,5 x 7 x 2,2 cm  7,2 cm SELV   

**0141/DALI**


**LED driver**  
IN: 110 - 240V  
OUT: 350 mA, 1-12 Power LED



11,1 x 5,2 x 2,5 cm  5,5 cm

  **0141/DIM**  
**LED driver**

IN: 110 - 240V  
OUT: 350 mA, 1-12 Power LED




Versione PUSH non sincronizzabile - PUSH version not synchronizable

11,1 x 5,2 x 2,5 cm  5,5 cm    

**0145 Dimmer Led Maxi**  
**Multipower dimmable driver**


IN: 110 - 240V  
OUT: 350 mA, 1- 21 power LED



12,3 x 8 x 2,2 cm  8,4 cm SELV    

**0145/DALI Dimmer Led Maxi**  
**Multipower dimmable driver**


IN: 110 - 240V  
OUT: 350 mA, 1- 21 power LED



12,3 x 8 x 2,2 cm  8,4 cm SELV     

**0133**


Cavo di sincronizzazione per dimmer LED  
Synchronization cable for dimmer LED  
(art. 0129 - art. 0129/DALI - art. 0145 - art. 0145/DALI)



L 150 cm

**0726/DIM**


**LED dimmer**  
TAGLIO DI FASE (IGBT-TRIAC, TRAILING EDGE-LEADING EDGE)  
PHASE CUT-OFF (IGBT-TRIAC, TRAILING EDGE-LEADING EDGE)  
IN: 220 - 240V  
OUT: 24V - 20W  
350 mA, 1-12 Power LED



16,5 x 4,5 x 3,5 cm  5,6 cm  IGBT-TRIAC  SELV

**IP LED DRIVERS** in corrente continua  
**IP LED DRIVERS** constant current**0031/IP**

**LED driver**  
IN: 220 - 240V  
OUT: 350 mA  
1-12 Power LED 1W



3,9 x 8 x 2 cm  4,2 cm IP67 SELV



La presente scheda tecnica è di proprietà di EGOLUCE srl. Tutti i diritti sono riservati. Le fotografie, le descrizioni degli apparecchi, disegni quotati ed i valori fotometrici menzionati sono a titolo indicativo e non costituiscono alcun impegno per la nostra società che si riserva di apportare, in qualsiasi momento e senza preavviso, tutte le modifiche che riterrà opportune.

EGOLUCE s.r.l, via I.Newton 12 - 20016 Pero - Milano  
telefono +39 02 339586.1 - fax. +39 02 3535112  
e-mail: info@egoluce.com - http://www.egoluce.com